



Shell Vacuum Pump Oil S3_{RX 100}

- Extra Protection
- Standard Applications

Rotary Vacuum Pump Oil

Shell Vacuum Pump Oil S3 RX 100 is formulated from selected premium performance, highly refined mineral oils. This provides the very low vapour pressure and high performance, desired for the effective lubrication of rotary vacuum pumps.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Long oil life – maintenance saving**
Shell Vacuum Pump Oil S3 RX 100 is formulated to provide excellent resistance to oil degradation. This ensures the oil will provide a long service life as well as reduced tendency for sludge build up and deposit formation.
- **Outstanding wear & corrosion protection**
Shell Vacuum Pump Oil S3 RX 100 helps provide effective protection of internal metal surfaces from corrosion and wear.
- **Maintaining system efficiency**
The selection of very low vapour pressure base oil with a narrow boiling range enables the pump to efficiently work at the vacuum for which it is designed over the extended maintenance period. The product also ensures protection against foaming.

Main Applications



- Rotary vacuum pumps

Shell Vacuum Pump Oil S3 RX 100 is designed for the use in rotary and sliding vane vacuum pumps. It can be used to provide low to medium vacuum pressures.

It is suitable for most laboratory and industrial rotary vacuum pump applications.

- **Standard operating environments**

Shell Vacuum Pump Oil S3 RX 100 is suitable for applications where ambient temperatures are above 0°C and where maximum operating temperatures do not exceed 100°C. Maximum vacuum pressure capability generally tends to decrease as the pump operating temperatures increase.

Shell Vacuum Pump Oil S3 RX 100 is suitable for vacuum pumps working in a vacuum range of 1 mbar – 10⁻³ mbar.

Shell Vacuum Pump Oil S3 RX 100 is not recommended for use when corrosive gasses or chemical vapours are involved in the extraction process.

Specifications, Approvals & Recommendations

- ISO 6743-3A-DVC.
- Shell Vacuum Pump Oil S3 RX 100 has been used extensively by major OEMs throughout the world.

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Typical Physical Characteristics

Properties		Method	Shell Vacuum Pump Oil S3 RX 100
ISO Viscosity Grade		ISO 3448	100
Kinematic Viscosity	@40°C cSt	ASTM D445	95
Kinematic Viscosity	@100°C cSt	ASTM D445	11
Density	@15°C kg/m ³	ASTM D1298	866
Flash Point COC	°C	ASTM D92	260
Pour Point	°C	ASTM D97	-9
Neutralisation Value	mg KOH/g	ASTM D947	<0.03
Ash, Sulphated	%	DIN 51575	<0.01

Properties		Method	Shell Vacuum Pump Oil S3 RX 100
Conradson Carbon Residue	%m	DIN 51551	0.05
Vapour Pressure versus Temperature, Isoteniscope	@0°C mbar	ASTM D2879	4.67E-09
Vapour Pressure versus Temperature, Isoteniscope	@25°C mbar	ASTM D2879	1.73E-07
Vapour Pressure versus Temperature, Isoteniscope	@50°C mbar	ASTM D2879	3.33E-06
Vapour Pressure versus Temperature, Isoteniscope	@100°C mbar	ASTM D2879	3.73E-04
Vapour Pressure versus Temperature, Isoteniscope	@150°C mbar	ASTM D2879	0.01
Vapour Pressure versus Temperature, Isoteniscope	@200°C mbar	ASTM D2879	0.24

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Vacuum Pump Oil S3 RX 100 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.