



Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Revision date: 03/07/2020 Supersedes: 18/12/2017 Version: 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Eni Rotra Multigear 75W-80
Product code	: 5556
Type of product	: Lubricants
Formula	: 0049-2016
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Non-dispersive use
Use of the substance/mixture	: Gearbox lubricant ---- Do not use the product for any purposes that have not been advised by the manufacturer.
Function or use category	: Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ENI S.p.A.
P.le E. Mattei 1 - 00144 Rome Italy
Phone: (+39) 06 59821
www.eni.com

Contact:
Refining & Marketing

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

1.4. Emergency telephone number

Emergency number	: CNIT +39 0382 24444 (24h) (IT + EN)
	Poison centre (UK): National Poisons Information Service Edinburgh (24h) (+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Skin sensitisation, Category 1 H317

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

CLP Signal word :

Warning

Hazardous ingredients and/or with relevant occupational exposure limits :

2-ethylhexyl methacrylate; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Hazard statements (CLP) :

H317 - May cause an allergic skin reaction.

Precautionary statements (CLP) :

P102 - Keep out of reach of children.
P261 - Avoid breathing mist, spray, Vapours.
P280 - Wear protective gloves, protective clothing.
P302+P352 - If on skin: Wash with plenty of soap and water.
P333+P313 - If skin irritation or rash occurs, get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash before reuse.
P501 - Dispose of contents and container to according to national or local regulations.

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification :

This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes :

Composition/ Information on ingredients:

Mixture of hydrocarbons

Additives

Metacrylic polymer

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (see note [**], see note [***])	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	75 - 85	Not classified
Mineral base oil, severely refined (For identification of the substance, see note [**], see note [***])		3 - 7	Not classified
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (see note [**], see note [***])	(CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (EC Index-No.) 649-483-00-5 (REACH-no) 01-2119474889-13	1 - 5	Not classified
Bis(nonylphenyl)amine (Additive)	(CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (EC Index-No.) N/A (REACH-no) 01-2119488911-28	1 - 1,5	Aquatic Chronic 3, H412
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (Additive)	(EC-No.) 931-384-6 (EC Index-No.) N/A (REACH-no) 01-2119493620-38	1 - 1,5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

2-ethylhexyl methacrylate (Additive)	(CAS-No.) 688-84-6 (EC-No.) 211-708-6 (EC Index-No.) N/A (REACH-no) 01-2119490166-35	0,1 - 0,2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
---	---	-----------	--

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (Additive)	(EC-No.) 931-384-6 (EC Index-No.) N/A (REACH-no) 01-2119493620-38	(50 <C <= 100) Eye Dam. 1, H318

Notes : [*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):
CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx.
All these substances have a value < 3 % wt of DMSO extract, according to IP 346/92 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)
Note [**]:
this product has a value of DMSO extract < 3 % wt, according to IP 346/92. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.
Note [***]:
substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.

First-aid measures after skin contact : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin irritation or rash occurs, get medical advice/attention. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Body hypothermia must be avoided. Do not put ice on the burn.

First-aid measures after eye contact : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor.

First-aid measures after ingestion : Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.

Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause sensitization by skin contact. Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact : Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.

Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.

Symptoms/effects upon intravenous administration : No information available.

Chronic symptoms : None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H₂S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).
- Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.
- Explosion hazard : In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m³ of air.
- Hazardous decomposition products in case of fire : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NO_x, H₂S and SO_x (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). PO_x.

5.3. Advice for firefighters

- Firefighting instructions : Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.
- Special protective equipment for firefighters : Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.
- Other information : In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material.

6.1.1. For non-emergency personnel

- Protective equipment : See Section 8.
- Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

- Protective equipment : Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. If necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Work helmet. Antistatic non-skid safety shoes or boots. Goggles and/or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H₂S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
- Emergency procedures : Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

- For containment : Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Other information : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Hygiene measures : Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

Incompatible products : Keep away from: strong oxidants.

Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product. Empty containers may contain combustible product residues. Do not weld, solder, drill, cut or incinerate empty containers, unless they have been properly cleaned.

Packaging materials : For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria	MAK (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary	AK-érték	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Netherlands	MAC TGG 8h (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-ED (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-EC (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Sweden	Nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Kortidsvärde (KTV) (mg/m ³)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Mineral base oil, severely refined		
Austria	MAK (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary	AK-érték	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Netherlands	MAC TGG 8h (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-ED (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-EC (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Kortidsvärde (KTV) (mg/m ³)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VECD (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Austria	MAK (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (langvarig) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark	Grænseværdi (kortvarig) (mg/m ³)	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Hungary	AK-érték	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Netherlands	MAC TGG 8h (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-ED (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain	VLA-EC (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Nivågränsvärde (NVG) (mg/m ³)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden	Kortidsvärde (KTV) (mg/m ³)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom	WEL STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VECD (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Canada (Quebec)	VEMP (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-TWA (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH	ACGIH TLV®-STEL (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Monitoring methods

Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts, Refer to relevant legislation and in any case to the good practice of industrial hygiene.
--------------------	--

Eni Rotra Multigear 75W-80

DNEL/DMEL (additional information)

Additional information Not applicable

PNEC (additional information)

Additional information Not applicable

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 1 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 2,7 mg/m³

Long-term - local effects, inhalation 5,6 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 0,74 mg/kg bodyweight/day

Long-term - local effects, inhalation 1,2 mg/m³/day

PNEC (Oral)

PNEC oral (secondary poisoning) 9,33 mg/kg food

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal 0,97 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 2,73 mg/m³

Long-term - local effects, inhalation 5,58 mg/m³

DNEL/DMEL (General population)

Long-term - systemic effects, oral 0,74 mg/kg bodyweight/day

Long-term - local effects, inhalation 1,19 mg/m³

PNEC (Oral)

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
PNEC oral (secondary poisoning)	9,33 mg/kg food
Bis(nonylphenyl)amine (36878-20-3)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	5 mg/kg bodyweight/day
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,25 mg/kg bodyweight/day
Long-term - systemic effects, dermal	2,5 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0,1 mg/l
PNEC aqua (marine water)	0,01 mg/l
PNEC aqua (intermittent, freshwater)	1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	132000 mg/kg dwt
PNEC sediment (marine water)	13200 mg/kg dwt
PNEC (Soil)	
PNEC soil	263000 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1 mg/l
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	12,5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	8,56 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0,25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,2 mg/m ³
Long-term - systemic effects, dermal	6,25 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	1,2 µg/l
PNEC aqua (marine water)	0,12 µg/l
PNEC aqua (intermittent, freshwater)	85 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	14,4 mg/kg dwt
PNEC sediment (marine water)	1,44 mg/kg dwt
PNEC (Soil)	
PNEC soil	2,94 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	10 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	24,33 mg/l
2-ethylhexyl methacrylate (688-84-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,5 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	3,48 µg/l
PNEC aqua (marine water)	0,348 µg/l
PNEC aqua (intermittent, freshwater)	21,8 µg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	2,24 mg/kg dwt
PNEC sediment (marine water)	0,224 mg/kg dwt
PNEC (Soil)	
PNEC soil	446 µg/kg dw
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

Hand protection:

Protective gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H₂S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

Personal protective equipment symbol(s):



Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Environmental exposure controls:

Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Wear protective gloves.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid, bright & clear.
Colour : Yellow-brown.
Odour : Slight odour of petroleum.
Odour threshold : There are no data available on the preparation/mixture itself.

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: Negligible.
Melting point	: -42 °C (pour point) (ASTM D 97)
Freezing point	: -60 - 0 °C (CAS 64742-54-7)
Boiling point	: >= 315 °C (CAS 64742-54-7)
Flash point	: 230 °C (ASTM D 92)
Critical temperature	: Not applicable for mixtures
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: ≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Critical pressure	: Not applicable for mixtures
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 880 kg/m ³ (15 °C) (ASTM D 1298)
Solubility	: Water: Immiscible and insoluble
Log Pow	: Not applicable for mixtures
Log Kow	: Not applicable for mixtures
Viscosity, kinematic	: 55,9 mm ² /s (40 °C) (ASTM D 445)
Viscosity, dynamic	: No data available
Explosive properties	: None (according to composition).
Oxidising properties	: None (according to composition).
Explosive limits	: LEL ≥ 45 g/m ³ (mineral oil mists)

9.2. Other information

Additional information : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H₂S. See also Section 16, "Other information".

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403)

Mineral base oil, severely refined

LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401)
---------------	------------------------------------

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Mineral base oil, severely refined	
LD50 dermal rat	> 5000 mg/kg bodyweight (OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (OECD 403)
Bis(nonylphenyl)amine (36878-20-3)	
LD50 oral rat	≥ 2000 mg/kg bodyweight (OECD 401)
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
LD50 oral rat	≈ 2000 mg/kg bodyweight
2-ethylhexyl methacrylate (688-84-6)	
LD50 oral rat	> 2000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable.
Additional information	: (according to composition)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable.
Additional information	: (according to composition) This product contains components with a Specific Concentration Limit (SCL). This product is formulated with a component which contains substances classified as Eye Dam.1, H318. The component itself has been tested by the manufacturer and has been assessed as NOT irritant to eyes. This result has been used for classification of the final mixture (Bridging principle "Dilution"). Expert judgment provided by the supplier
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Additional information	: (according to composition) This product contains one or more components (2-ethylhexyl methacrylate, Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)) classified as sensitizers. Causes sensitisation
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition) This product contains : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil, and; solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil having a viscosity of approximately 112cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346/92. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346/92 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3) No carcinogenic effect
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Mineral base oil, severely refined	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
NOAEL (subacute, oral, animal/male, 28 days)	150 mg/kg bodyweight
2-ethylhexyl methacrylate (688-84-6)	
NOAEL (oral, rat, 90 days)	120 mg/kg bodyweight/day
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition) Viscosity, kinematic: > 20,5 mm ² /s (40 °C) (ASTM D 445)
Eni Rotra Multigear 75W-80	
Viscosity, kinematic	55,9 mm ² /s (40 °C) (ASTM D 445)
Potential adverse human health effects and symptoms	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause sensitization by skin contact. Contact with eyes may cause temporary reddening and irritation.
Other information	: None.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.
Ecology - air	: This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists.
Ecology - water	: This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Not classified (Based on available data, the classification criteria are not met)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Mineral base oil, severely refined	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Bis(nonylphenyl)amine (36878-20-3)	
LC50 fish 1	≥ 100 mg/l (OECD 203)
EC50 Daphnia 1	≥ 100 mg/l (OECD 202)
ErC50 (algae)	≥ 100 mg/l (OECD 201; 96h; Scenedesmus capricornutum)
ErC50 (other aquatic plants)	600 mg/l (OECD 201; 96h; Pseudokirchneriella subcapitata)
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	
LC50 fish 1	24 mg/l (Rainbow Trout)
LC50 fish 2	8,5 (Fathead Minnow)
EC50 Daphnia 1	91,4 mg/l
EC50 72h algae (1)	6,4 - 15 mg/l
EC50 96h algae (1)	6,4 mg/l (Selenastrum Capricornutum)
NOEC (acute)	1,7 - 3,3

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

NOEC chronic fish	3,2 mg/l (Rainbow Trout - 4d)
NOEC chronic crustacea	0,12 mg/l (Daphnia magna - 21 d)

2-ethylhexyl methacrylate (688-84-6)

LC50 fish 1	2,78 mg/l (Oryzias latipes, 4 d)
EC50 Daphnia 1	0,105 mg/l
EC50 72h algae (1)	7,68 - 1260 mg/l
NOEC (acute)	0,105 mg/l (Daphnia magna)
NOEC chronic crustacea	0,105 mg/l

12.2. Persistence and degradability

Eni Rotra Multigear 75W-80

Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
-------------------------------	--

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
-------------------------------	--

Mineral base oil, severely refined

Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
-------------------------------	--

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
-------------------------------	--

Bis(nonylphenyl)amine (36878-20-3)

Persistence and degradability	Not biodegradable.
Biodegradation	1 % (28d)

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Biodegradation	3,6 - 7,4 % (28d - OECD 301 B)
----------------	--------------------------------

2-ethylhexyl methacrylate (688-84-6)

Biodegradation	88 % (28d) (OECD TG 301 C)
----------------	----------------------------

12.3. Bioaccumulative potential

Eni Rotra Multigear 75W-80

Log Pow	Not applicable for mixtures
Log Kow	Not applicable for mixtures
Bioaccumulative potential	Not established.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

Log Kow	> 6
---------	-----

Bis(nonylphenyl)amine (36878-20-3)

Log Pow	> 7,6
---------	-------

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Log Kow	5,14 (25°C)
---------	-------------

2-ethylhexyl methacrylate (688-84-6)

Bioconcentration factor (BCF REACH)	37
Log Kow	4,95

12.4. Mobility in soil

Eni Rotra Multigear 75W-80

Ecology - soil	No data available.
----------------	--------------------

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

12.5. Results of PBT and vPvB assessment

Eni Rotra Multigear 75W-80	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Component	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Mineral base oil, severely refined ()	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

12.6. Other adverse effects

Other adverse effects	: None.
Additional information	: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.
Sewage disposal recommendations	: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.
Ecology - waste materials	: The product as it is does not contain halogenated substances.
EURAL code (EWC)	: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADN / ADR / IATA / IMDG / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
None.				

14.6. Special precautions for user

- Overland transport

Not regulated

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

- Transport by sea

Not regulated

- Air transport

Not regulated

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Eni Rotra Multigear 75W-80 - 2-ethylhexyl methacrylate - Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	2-ethylhexyl methacrylate - Bis(nonylphenyl)amine - Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directives 75/439/CEE - 87/101/CEE concerning disposal of used oils.

France

Maladies professionnelles (F) : RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse

Germany

Reference to AwSV : Water hazard class (WGK) (D) 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

WGK remark : Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBl 2017, Teil I, Nr. 22, Seite 905).

VbF class (D) : Not applicable.

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Storage class (LGK) (D)	: LGK 10 - Combustible liquids
Employment restrictions	: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)
Other information, restrictions and prohibition regulations	: TRGS 400: Hazard assessment for activities involving Hazardous Substances TRGS 401: Risks resulting from skin contact - identification, assessment, measures TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure TRGS 500: Protective measures TRGS 555: Working instruction and information for workers TRGS 800: Fire protection measures TRGS 900: Occupational Exposure Limits

Netherlands

Saneringsinspanningen	: C - Minimize discharge
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed

Denmark

Danish National Regulations	: Young people under 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it
-----------------------------	---

15.2. Chemical safety assessment

For this mixture a chemical safety assessment has been not carried out

A chemical safety assessment has been carried out for the following components of this mixture:

2-ethylhexyl methacrylate
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
Baseoil - unspecified
Distillates (petroleum), hydrotreated heavy paraffinic
Bis(nonylphenyl)amine
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Notes
1.1	Formula	Modified	
1.1	Type of product	Added	
1.2	Industrial/Professional use spec	Added	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.3	Other hazards not contributing to the classification	Modified	
3	Composition/information on ingredients	Modified	
3.2	Comments	Added	
3.2	Notes	Added	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures general	Removed	
4.1	First-aid measures after skin contact	Modified	
4.2	Symptoms/effects after ingestion	Modified	
4.3	Other medical advice or treatment	Modified	

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

5.2	Hazardous decomposition products in case of fire	Added	
5.3	Special protective equipment for firefighters	Modified	
5.3	Firefighting instructions	Modified	
6.1	Protective equipment	Modified	
7.1	Precautions for safe handling	Modified	
7.1	Hygiene measures	Modified	
7.2	Storage temperature	Removed	
8.1	DNEL/DMEL and PNEC values	Added	
8.2	Appropriate engineering controls	Modified	
9.1	Freezing point	Added	
9.1	Boiling point	Added	
9.1	Flammability (solid, gas)	Added	
9.1	Melting point	Modified	
9.1	Flash point	Modified	
9.1	Viscosity, kinematic	Modified	
9.1	Critical temperature	Added	
9.1	Critical pressure	Added	
9.1	Log Kow	Added	
9.1	Oxidising properties	Modified	
9.1	Explosive properties	Modified	
9.1	Molecular mass	Removed	
10.4	Conditions to avoid	Modified	
11.1	Additional information	Modified	
11.1	Additional information	Modified	
12.3	Log Kow	Added	
14.2	Proper Shipping Name	Removed	
14.6	Special transport precautions	Removed	
15.1	Other information, restrictions and prohibition regulations	Added	
15.1	Employment restrictions	Added	
15.1	Water hazard class (WGK) (D)	Modified	
15.1	WGK remark	Modified	
15.1	Storage class (LGK) (D)	Modified	
15.1	REACH Annex XVII	Modified	
15.1	Other information, restriction and prohibition regulations	Added	
16	Other information	Modified	
16	Indication of changes	Added	

Abbreviations and acronyms:

	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/A = not applicable
	N/D = not available
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Effective concentration for 50 percent of test population (median effective concentration)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

Eni Rotra Multigear 75W-80

Safety Data Sheet

According to Regulation (EU) No. 830/2015

PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways
SDS	Safety Data Sheet
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Data sources	: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Training advice	: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H ₂ S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H ₂ S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H ₂ S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. Therefore, it is very important to follow the above mentioned precautionary measures also with used oils.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Sens. 1	H317	Concentration limits
--------------	------	----------------------

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.